

SAM4S

Robust Cube Series

Hcube




Standard and Powerful POS Printer

- Fast printing speed 230mm/s
- Backlight logo design and glossy finished top cover
- Three LEDs for visualizing printer status (power, paper, error)
- Various Interface (USB, Serial, Ethernet and Wi-Fi)
- Desktop and Wall-mounted supported
- 100km TPH lifespan and 1.5 million cuts
- Kitchen bell sound adjustable by firmware




Interface layout

▲ USB+Serial+Ethernet



▲ USB+Serial



▲ USB+WIFI(Bluetooth)



Available Options



Specification

Model		HCUBE-100
Printing Parameters	Print Method	Direct Thermal
	Resolution	Default 203 dpi
	Print Width	72mm (576dots)
	Print Speed	Max. 230 mm/s
Interfaces	Default	USB + Serial + Ethernet + Drawer
	Option	USB + Wi-Fi + Bluetooth
Auto Cutter		Only Partial Cut
Page Mode		Yes
Memory	RAM	4 MB
	Flash	4 MB
Barcode	1D	UPC-A, UPC-E, CODE39, CODE93, CODE128, EAN128, EAN8, EAN13, ITF, CODABAR
	2D	PDF417, QR code
Paper	Paper Width	79.5±0.5mm / 57.5±0.5mm
	Paper Roll Diameter	Max Φ 83.0mm
Reliability	TPH	100 km
	Auto Cutter	1.5 Million Cuts
Option	Kitchen bell	Yes (External Type)
	Partition	Yes
Software	Emulation	ESC/POS
	Driver/ Utility	Windows Driver, OPOS Driver, JPOS Driver (Linux&Windows), CUPS Driver (Linux&Mac), Utility Program
	SDK	Windows, Android, IOS SDK
	OS	Windows XP / Win7 / Win8 / Win10 / Win11, Win Server, POSReady, Linux, MAC
Sensor		Paper out, Cover open
Power Supply	Input	AC 100~240V/50~60Hz
	Output	DC 24V±5%, 1.5A
Dimensions (W*D*H) & Weight		140(W)*179(D)*117(H)mm / 0.92Kg
Accessory		Power Adaptor, Power Cord, Quick Guide, USB Cable