

ZED 2602

Cabled 2D Barcode Scanner



Now entering the third generation of the ZED 2600 series of 1D/2D hand held barcode scanners the 2602 just keeps on getting better!

Stylishly designed the 2602 complements rather than detracts from retail store fitouts and is equally at home in other commercial barcode scanning applications.

With Nexa's signature 3 year replacement warranty included, the 2602 is a secure investment.

Whether you need to scan hands-free or prefer hand-held the ZED 2602 delivers.

It adapts to any environment and offers a fast versatile scanning solution.

Hands free stand included.

3

year replacement
warranty



Able to read
2D (QR) Barcodes



**Fast Scan
Performance**

Specifications

Image sensor	CMOS
Image Sensor Resolution	640x480 Pixels
Light source	White LED(lighting) red LED aiming
CPU	ARM, 32bit
Scan speed	60 frames per second
Minimum Resolution	≥3mil
Decoding Range	60-360mm (13mil PCS90%)
Scanning Angle	Skew / Pitch ± 65 °
Scan Mode	Manual trigger or Presentation mode
Decoding Capability	1D:Codabar, Code11, Code39, Code32, Interleaved 2 of 5, Industrial 2 of 5, Matrix 2 of 5, Code93, Code128, GS1-128, UPC-A, UPC-E, EAN 8, EAN 13, GS1 DataBar (RSS14), GS1 DataBar Limited, GS1 DataBar Expanded, etc 2D: PDF417, Micro PDF417, QR Code, Micro QR, Data Matrix, Aztec Code
Interface	USB, USB-Virtual Com Port
Scanner size	163 (L) x 68 (W) x 80 (H) (mm)
Scanner weight	185g
Material	ABS+TPU
Input voltage	DC 3.6V-5.5V
Working current	142mah
Stand-by current	42mah
Indicator	Ring LED indicator light, buzzer
Cable standard	Straight: 1.5m
Temperature	(Operating) -10°C to 50°C
Humidity	Relative humidity 5%-95%(no condensation)
Temperature	(Storage) -20°C to 60°C
Light Source	0-5000Lux(fluorescent), 0-100,000Lux(Sunlight)

Nexa ZED 2602 Data Sheet | Rev A | Jan-24. © 2024. Features and specifications subject to change without notice.